

SuperEar® PERSONAL SOUND AMPLIFIER

LCS120C	SIZE	UNITS / WEIGHT	HS TARIFF CODE
REMAIL	10" x 7.0" x 2.5"	1 / 2.0 lbs	8525. 60. 2000



LCS120. Television and Tour Set

PRODUCT HIGHLIGHTS

- 3 Year Warranty
- Up to 150 ft. Wireless Audio
- 3 FM channels
- Broadcast to multiple receivers



LCS120C Set includes:

- a) Owner's Manual
- b) 2 LCR100 Receiver units
- c) 1 LCT100 Transmitter unit
- d) 3 Belt Clips
- e) 2 Sets of Stereo Earbuds
- f) 6-AA Ni-MH Rechargeable batteries
- g) 2-USB port Charging Cube and 2 USB Cables
- h) Clip-on Microphone Assembly
- i) 3.5mm jack to 3.5mm jack Cable
- j) 1 Zippered, Pocketed Vinyl EV ACase

LCT100 TRANSMITTER UNIT

Microphone	50dB gain, multielement, integrated
Body frame material	High Impact ABS
Max Output	107 dB
Humidity Operating Range:	At 20°C, 95% RH
Dimensions	3.05" x 2" x 0.75"
Frequency Switch	3-position, user selectable
Plug-in connector	Stereo jack, 3.5mm diameter
Power Source	2-AA Ni-MH batteries (rechargeable)
Dual USB Charger	110/240VAC, USB to Mini-B jack
Operation time	Approx. 11 hours between recharge
Belt/Pocket/Clip	included
3.5 mm Audio-in connector	for connecting external audio sources such as TV, Computer, Ipod®, etc.

LCR100 RECEIVER UNIT

Automatic Shut Off	No
Body frame material	High Impact ABS
Max Output	107 dB
Reception distance	Up to 150 ft
Frequency Switch	72.2, 72.8 and 75.8 MHz, selectable
Frequency Range	100Hz -14KHz
Plug-in connector	Stereo jack, 3.5mm diameter
Power Source	2-AA Ni-MH batteries (rechargeable)
Weight	3 oz.
Belt/Pocket/Clip	included

EARBUDS (LC-EB)

Diaphragm	Mylar, diameter 10mm.
Impedance	32 ohms +- 15% at 1KHz
Nominal Power	5mW
Max Power	10mW
Sensitivity	105 dB S.P.L +- 3dB at 1KHz
Balance per channel	+ - 3dB at 1KHz
Frequency Response	20Hz-20 KHz
Plug-in connector	Stereo Plug, 3.5mm diameter
Cord Length	1150mm +- 50mm
THD	Less than 5% at 1KHz 0.126V